

**DESCRIPTION: All for Stone Enhance'N'Seal WB™ (Water-Based)**

is a solvent-free, below surface, sealer formulated to provide excellent stain resistance and also to enhance & highlight the natural colours of porous, unsealed surfaces. Allows Moisture Vapour Transmission (MVT). For interior and exterior use.

**USES:** UNSEALED porous natural stone, grout, concrete, pavers, brick, unglazed, porous tiles etc. Suitable for driveways, patios, steps, walls or floors. Excellent darkening characteristics for faded black limestone.

**TEST FIRST:** Due to the nature of different surfaces conduct several tests in inconspicuous areas in accordance with the label instructions to determine application method, number of coats and desired results. The end user must determine the suitability of the product for their intended use.

**PRE-GROUT SEALING:** This will allow quick & easy clean up after grouting as grout may stain surfaces. Do not saturate the open grout joints. Follow application instructions below.

**PRECAUTIONS:** 1. Always test first. 2. Read entire label and product technical data sheet before using. 3. Wear appropriate skin and eye protection and use in a well ventilated area. 4. Surface must be clean, free of contamination and completely dry and free from any other sealers and coatings. 5. Use when surface temperature is between 4°C and 32°C. **6. Once surface has been enhanced it cannot be restored to its original look.**

**INSTRUCTIONS:** 1. Sweep, vacuum or wipe surface; 2. Shake Bottle well, apply product using a, paint pad, brush, sealer-sponge, floor-finish applicator or spray. 3 Apply to saturation point in one application. If additional coats are required, apply 'wet-on-wet' 4. Do not allow to pool, remove any remaining surplus sealer after 15-20 minutes. Buff Dry – Do not allow the product to dry on the surface.

**LIMITATIONS:**

- Do not allow the product to come into contact with any non-recommended surface
- Regular use of harsh cleaning chemicals will affect the performance and enhancement
- Sealer will not prevent surface wear or etching from harsh chemicals
- Do NOT apply other sealers, coatings or finishes over Enhance 'N' Seal WB™

**EXPECTED WEAR:** Up to 15 years but will vary depending on texture, & hardness of surface, surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, alkaline, acidic and solvent based cleaners and weather exposure will affect wear and performance. Re-seal as required.

**COVERAGE:** Approximately 6 to 16m<sup>2</sup> per litre per coat. Typically only one coat required in most situations. Coverage varies depending on type of surface, & its porosity, texture and finish.

**MAINTENANCE:**

- All for stone EzyClean™ for routine everyday maintenance
- All for Stone XtremeClean™ for periodic heavy duty cleaning

**HANDLING AND STORAGE:**

- Close container tightly after each use. Store in original container only
- Store and use in temperatures between 4°C and 32°C.

**FIRST AID:**

Eye Contact:	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice.
Skin Contact:	Remove contaminated clothing. Wash skin with soap and water or use a proprietary skin cleanser.
Inhalation:	Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
Ingestion:	Wash mouth out with water and give warm milk to drink. Seek medical attention. Do not induce vomiting.

**SAFETY INSTRUCTIONS:** Avoid contact with skin and eyes. For full safety details consult MSDS