



Essential tips and facts about Enhance 'N' Seal

Thank you for considering Enhance 'N' Seal, it is an incredibly high-performance sealer and enhancer. However, there are a few key points to note in order to ensure a successful application of the product:

- **TEST** – always conduct a small test in an inconspicuous area to satisfy yourself that the product provides the results you are looking for as it is not reversible after application.
- Do not leave excess product to dry on the surface, remove with absorbent material **before** it dries. In other words, make sure to leave the SURFACE completely dry and free of product. Enhancers are often described as 'wet-look' but this refers to the effect of having a darker colour, as a result of wetting, and NOT a shiny/glossy 'wet' surface.
- This type of product is best suited to previously unsealed stone, tiles or grout. Use of the product on stone that has previously been sealed, or oiled /waxed even if this has been stripped back, is not recommended.
- Control of moisture is **critical**.
 - The product, when cured is extremely resistant to moisture and water (one of the reasons it is such a good sealer).
 - However it **MUST NOT** come into contact with moisture before, during and for a period after application, until it has fully cured.
 - Surface being treated must be dry before you commence application – consider subfloor circumstances in older properties with no DPC - if in doubt, use a moisture metre to ensure there is no moisture present before proceeding. Bear in mind recently cleaned or washed surfaces may still hold moisture even after the surface appears dry.
 - Keep all sealed surfaces dry for at least 12 to 24 hours after application
 - If using in external situations, make sure there is going to be a period of several consecutive days of dry weather after application, and/ or take precautions to cover/protect from wet weather – allow a few centimetres clearance between any covering and the surface being sealed. For this reason it is best to apply this product in external situations over the summer months
- If you require further technical assistance or advice before proceeding, please call 01244 819939 or email sales@allforstone.co.uk
-

A short – haired paint-pad is the ideal method for application. But a microfiber cloth or lambswool floor finish applicator could also be used.

All for Stone Limited.