

DESCRIPTION

All For Stone[™] Grout Renue'N'Seal[™] is a modified waterborne epoxy formula designed to renew, re-colour and seal existing grout. Renue'N'Seal utilises the latest Rapid-Seal STC[™] Technology to provide maximum stain resistance in 24 hours. It is non flammable, non toxic, and easy to use. Allows Moisture Vapour Transmission (MVT). For interior and exterior use.

USES

Use on existing sanded, unsanded and epoxy grout where maximum stain resistance and uniform colour is desired.

TEST FIRST

Due to the nature of different surfaces, you should do several tests in inconspicuous areas according to the label instructions to determine application method, number of coats & desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. Always Test first;

- 2. Read entire label & product technical bulletin before using;
- 3. Wear appropriate skin protection.

4. Surface must be clean & completely dry and free from any other sealers & coatings;

5. Use when surface temperature is between 4°C & 32°C;

6. If using more than 1 bottle of a single colour, mix all the material to be

used together in a large container to ensure colour uniformity. 7. Ensure that existing grout sits lower than the tile surface.

 Porous surrounding surfaces may require sealing to ensure product is not absorbed;

9. For use in shower cubicles, the use of a moisture meter can help determine when the existing grout is dry and ready to apply product.

PREPARATION OF EXISTING GROUT JOINT

Use All For Stone[™] XtremeClean as per label instructions to clean and prepare existing grout joints. For smooth or latex modified grout joints, Grout Haze Plus [™] to clean and create texture on existing grout joint (do not use acids on acid sensitive stone).

INSTRUCTIONS

1. SHAKE WELL BEFORE USING;

Ensure surface is completely dry then sweep, vacuum, or wipe surface;
Apply small amount of product directly onto grout joint;

4. Work the product along the grout joint in a back-forward motion using an Grout Renue'N'Seal™ Applicator Brush or a toothbrush;

5. Ensure a thin even coat is applied and minimise the amount spread on to tile surface;

6. Allow product to dry a minimum 30 minutes (touch dry) then mist a small amount of water on the surface; (Do not allow product to dry on tile surface for longer than 12 hours);

7. Using a white nylon pad, remove excess product from the tile surface, ensuring that you do not scrub directly into the grout joint;

8. The surface is ready for light traffic after 2 hours. Keep surface dry for 24 hours. Note: When using contrasting colours, more than 1 coat might be necessary with a drying time of 2 hours between each coat. Follow label instructions for each coat.

COLOUR ACCURACY

Colour & shade variation can occur depending on job site, lighting, surface and surrounding conditions.

LIMITATIONS

• Do not use in under water or pooling water situations;

• Do not allow the product to come in contact with any non-recommended surfaces.

EXPECTED WEAR

Up to 20 years but will vary depending on texture & hardness of surface, surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners and weather exposure will affect wear and performance. Re-seal as necessary.

COVERAGE

The coverage will vary depending on size of joint, size of tile, density, porosity, texture, surface absorption, weather conditions, the application method and number of coats. As a guide per 237ml Bottle will seal 200x 200mm tile with 3mm joint – up to 30m2 per coat, 300x300mm tile with 3mm joint – up to 40m2 per coat. For full coverage chart refer to www.Groutrenuenseal.co.uk

MAINTENANCE

- All For Stone[™] EzyClean[™] for routine, everyday cleaning;
- All For Stone[™] XtremeClean[™] for periodic heavy duty cleaning;

HANDLING AND STORAGE

• Close container tightly after each use. Store in original container only.

• Store and use in temperatures between 4°C and 32°C.

FIRST AID

If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

SAFETY DIRECTIONS

Avoid contact with skin and eyes. Keep out of reach of children.

WARRANTY

All For Stone[™] "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any

way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST.



All For Stone Limited: Technical Support Phone +44 (0)1244 819939 or Email technical@allforstone.com www.allforstone.co.uk