



DESCRIPTION

All for Stone Ltd. "Strip-It™" is a safe, non-flammable, biodegradable, multi-purpose stripper formulated to stay wet for longer periods to give the product time to break down & help remove most sealers, coatings, epoxy grout haze, urethane coatings, synthetic finishes, adhesives, silicone, paint, heavy wax, deep-set stains and heavy grease build up.

USES

Use on all natural stone, grout, ceramic, porcelain, terracotta, Saltillo, quarry tiles, terrazzo, concrete, pavers & masonry etc

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. Always test first;
2. Read entire label, SDS & product technical bulletin before using;
3. Wear appropriate gloves, skin & eye protection & use in a well ventilated area or wear an appropriate mask;
4. Use when surface temperature is between 4°C and 32°C.
5. Do not mix with other chemicals or allow product to come in contact with any non-recommended surfaces;
6. Floor will get slippery during process. Take appropriate precautions to prevent slips or falls;
7. Will affect sealers, coatings, floor finishes & painted surfaces.

INSTRUCTIONS

1. Sweep, wipe or vacuum surface;
2. Carefully apply liberal amount of Strip-It™ to a small manageable area of up to 4m²;
3. Spread with a roller, mop, sponge or brush;
4. Allow product to dwell minimum 1 hour without drying or until coating or residue softens. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
5. Agitate with solvent resistant scrub pads, scrub brush or scrub machine;
6. Remove the residue with a wet vac or if thick, with clean, absorbent white cotton towels, scoop or shovel;
7. Rinse thoroughly with clean water;
8. Repeat the process as necessary;
9. Surface ready for light traffic in minimum 1 hour or after all fumes have dissipated.
10. Allow at least 48-hour drying time before applying any sealers, coatings or floor finishes. Always test first.

NOTE: To help with residue removal, apply XtremeClean™ diluted 1 part with 3 parts water to the surface after Step 6. Allow dwell time of 5-10 minutes then scrub or agitate. Remove with wet vac then continue with Step 7 onwards.

LIMITATIONS

- For epoxy grout haze removal, limit dwell time in Step 4 to no more than 30 minutes. Do NOT allow puddling in grout joints.
- Removal of thick coatings may require multiple applications.
- Will affect sealers, coatings and painted surfaces

COVERAGE

Approximately 10–40 square meters per litre. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

FIRST AID

If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a medical professional or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

SAFETY DIRECTIONS:

Avoid contact with skin and eyes. Wear protective gloves, eye & skin protection when using. Use in a well ventilated area or use a mask. Avoid breathing vapour or mist spray. May cause stomach distress, nausea or vomiting. May cause respiratory tract irritation.

WARRANTY

All For Stone™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS DO A TEST FIRST.**