ALGABAN Algae and Moss Remover

DESCRIPTION

All For Stone™ Algaban™ is a specially designed solution for removFing green algae, slime, moss and other plant derived deposits. Highly concentrated for a cost-effective treatment. Product is self-acting requires no scrubbing, is easy to use and has an ongoing regrowth-preventing effect. Particularly useful prior to repainting fence panels and the like.Contains no acids or chlorine. Not suitable for deep-set, ingrained black deposits and the like.

USES

Use on all. Concrete, brick, stone, masonry, render. steps, patios, paths, glass wood fence panels, roofing etc.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

- 1. Always Test first;
- 2. Read entire label and product technical bulletin before using;
- 3. Wear appropriate skin protection;
- 4. Use when surface temperature is between 4°C and 32°C.

INSTRUCTIONS

- 1. Shake well before using;
- 2. Sweep, vacuum, or wipe surface;
- 3. Dilute with water as follows: 1 part Algaban to 10 parts water (can dilute from 1:5 to 1:20 depending on degree of contamination);
- 4. Apply to surface with garden sprayer at approx. 0.2 ltrs per m2 (or by watering can)
- 5. Keep treated surfaces protected from rain for at least 4 hours. Rinse with water after several days.
- 6. Allow 24 to 48 hours for results to begin to show

LIMITATIONS

 Do not allow product to come in contact with any nonrecommended surfaces.

COVERAGE

Up to 150 m2 if applied by sprayer or 50m2 if applied directly by watering can

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

CAUTIONS, SAFETY AND FIRST AID







DANGER

- * Quaternary ammonium compounds, benzyl-C12-14 (evennumbered)-
- * alkyldimethyl, chlorides
- Hazard statements
- * H314 Causes severe skin burns and eye damage.
- * H302 Harmful if swallowed.
- * H410 Very toxic to aquatic life with long lasting effects.
- Precautionary statements
- * P273 Avoid release to the environment.
- * P280 Wear protective gloves/protective clothing/eye protection/face protection.
- * P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- * P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- * P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- * P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

WARRANTY

All For Stone™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. ALWAYS DO A TEST FIRST.

