

DESCRIPTION

All for Stone™ Xtreme Clean Neutral pH™ is a fast acting, concentrated, neutral pH cleaner & degreaser. It is designed to remove grease, grime, oil and ingrained dirt as well as light wax coatings, including factory applied wax coatings and designed-to-remove floor finishes. Ideal for areas that have been neglected or subject to heavy use and/or where high pH cleaners are not desirable.

USES

Use on all natural stone, grout, ceramic, porcelain, terracotta, saltillo, quarry tiles, terrazzo, concrete, pavers, masonry and other water safe surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. AVOID ALL SKIN CONTACT;
2. Always Test first;
3. Read entire label and product technical bulletin before using;
4. Wear appropriate skin and eye protection;
5. Use when surface temperature is between 4°C and 32°C.

INSTRUCTIONS

1. Sweep, vacuum, or wipe surface;
2. Dilute Xtreme Clean Neutral pH™ as follows:
 - a) LIGHT: Mix 10 parts water to 1 part product;
 - b) MODERATE: Mix 5 parts water to 1 part product;
 - c) HEAVY: Mix 3 parts water to 1 part product;
 - d) STRIPPING WAX: Mix 2 parts water to 1 part product;
3. Carefully apply the solution to pre-wet surface with a sponge or a mop;
4. Allow minimum dwell time of 10-15 minutes for cleaning or Longer for stripping - DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
5. Scrub with a white nylon pad, scrub brush or scrub machine;
6. Remove the dirty solution with a wet vac or mop;
7. Rinse thoroughly with clean water;
8. Repeat the process as necessary.

LIMITATIONS

- Do not allow product to come in contact with any non-recommended surfaces.
- Regular use of high alkaline cleaners will affect the performance of sealers.

COVERAGE

Approximately 10–30 square meters per litre. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

FIRST AID AND SAFETY DIRECTIONS: Avoid contact with skin and eyes.



Corrosive

Hazard Statements:

H302: Harmful if swallowed. H319: Causes serious eye irritation.

Precautionary Statements: P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

WARRANTY

All For Stone™ “The Manufacturer” warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer’s obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. ALWAYS DO A TEST FIRST.